

**BATCO** 





# FX SERIES

## FIELD LOADERS

1535 | 1545 | 2045

### SEE THE FX OF CHANGE ON THE BATCO FIELD LOADER.

The FX Series has been engineered for ease of maintenance, optimized containment and maximum speed. The FX Series is 50% faster than previous models reaching up to 9,000 bph for the 1500 Series and 14,000 bph for the 2000 Series. The optional heavy-duty mover tackles all terrains with ease and the modified hopper keeps grain where it needs to be - on the belt.

### FEATURES

- Bearings are positioned for reduced exposure, easy maintenance and serviceability
- Optimized containment
- Powder coat paint for a durable, long lasting finish
- 12.5" discharge hood to accommodate capacity

# 1500 SERIES

### FEATURES

- 15" wide belt, 10" tube diameter
- Available in 35' and 45' lengths
- Capacity up to 9,000 bu/hr

### DRIVE OPTIONS

#### S-DRIVE

- Gas (optional soft start electric clutch)
- Electric

#### UNDER MOUNT S-DRIVE (FX1545 only)

- Gas drive standard with soft start electric clutch



#### TOP DRIVE

- Hydraulic
- Electric

# 2000 SERIES

### FEATURES

- 20" wide belt, 14" tube diameter
- Available in 45' length
- Capacity up to 14,000 bu/hr

### DRIVE OPTIONS

#### S-DRIVE

- Gas
- Electric




### OPTIONAL HEAVY-DUTY MOVER KIT

- Single lift cylinder with supported heavy-duty slider for added rigidity and stability
- Hydraulic joystick controlled 4-wheel steering for effortless maneuverability
- Spring loaded walking axles to keep tires on the ground
- 6.5" wide all-terrain tires for added floatation to allow the unit to ride over rough terrain

### FX SERIES FIELD LOADER | SPECIFICATIONS

MODEL	BELT LENGTH	WEIGHT (LBS)	UP-OPERATION				DOWN-OPERATION				WIDTH	HP GAS	Hyd Motor CU/IN Req.
			A	B	C	D	A	B	C	D			
FX 1535 TD - Electric	83' 1"	1660	17'	15.4'	N/A	N/A	10'	16.6'	N/A	N/A	7.5'	N/A	N/A
FX 1535 TD - Hydraulic	83' 1"	1660	16.75'	16.8'	N/A	N/A	18.2'	14.7'	N/A	N/A	7.5'	N/A	6.2 (2000 SERIES)
FX 1545	107' 2"	2305	20.8'	21.6'	12'	14'	8.8'	22.1'	14'	16'	7.5'	32 HP	N/A
FX 1545 TD - Electric	103' 1"	1966	22.3'	21'	N/A	N/A	10.22'	21.4'	N/A	N/A	7.5'	N/A	N/A
FX 1545 TD - Hydraulic	103' 1"	1966	19.75'	23'	N/A	N/A	15.25'	24.25'	N/A	N/A	7.5'	N/A	6.2 (2000 SERIES)
FX 2045	114'	3775	20'	23.5'	11'	13'	13'	25'	14'	16'	8.4'	35 HP	N/A

"A" up-operation is conveyor discharge height (from bottom of discharge hood) at 30 degrees.  
 "A" down-operation is overall conveyor height (from top of discharge hood)



Box 1750, Swift Current Saskatchewan, Canada S9H 4J8  
 877.667.7421 | sales@batco-rem.com | batcomfg.com

Batco Conveyors. Belt to Last.

